

Product Code: TCIMVH-0170LFB

Item Description: 170L CYCLONE IND HG STANDARD B

B

- Manufactured from high grade Duplex stainless steel
- Fitted with Branded Quality Components
- Works with Air Source Heatpumps



Capacity	Brand	ERP Type	Item Category Code	Product Group Code	Model
170 L	CYCLONE	IndirectUnvented	Stainless	CYCLONE	HG INDIRECT

#### Product Specification

Actual capacity (Ltr)	168	Thermal insulation	DENSE PU FOAM
Unit weight empty (kg)	54	Cylinder material	LDX 2101
Unit weight full (kg)	223	Outer casing	COATED MILD STEEL
No immersions	1	Coil material	316L STAINLESS STEEL
Immersion spec	3KW@230V	Foam thickness	0
Max mains water pressure (Bar)	10	Operating temp (C)	60
Operating pressure (Bar)	7	Safety valve temp (C)	90
Tested to standard	BS EN 12897:2006	Warranty terms (Year)	1Y
No heat exchangers	1	Heat loss	1.32
Coil 1 rating (kW)	75.86	Coil 1 surface area (m <sup>2</sup> )	2.2
Coil 1 max prim pressure (Bar)	3.5	Coil 1 resistance (Bar)	.18



### Dimensions

A (mm)	1310
B (mm)	540
C (mm)	196
D (mm)	861
E (mm)	261
F (mm)	406
G (mm)	1031
H (mm)	1343
I (mm)	211

