



Product Code: TCIMVH-0200NFC

Item Description: 200L CYCLONE IND HG SHORT C

C

- Manufactured from high grade Duplex stainless steel
- Fitted with Branded Quality Components
- Works with Air Source Heatpumps



Capacity	Brand	ERP Type	Item Category Code	Product Group Code	Model
200 L	CYCLONE	IndirectUnvented	Stainless	CYCLONE	HG INDIRECT

Product Specification

Actual capacity (Ltr)	194	Thermal insulation	DENSE PU FOAM
Unit weight empty (kg)	57	Cylinder material	LDX 2101
Unit weight full (kg)	255	Outer casing	COATED MILD STEEL
No immersions	1	Coil material	316L STAINLESS STEEL
Immersion spec	3KW@230V	Foam thickness	0
Max mains water pressure (Bar)	10	Operating temp (C)	60
Operating pressure (Bar)	7	Safety valve temp (C)	90
Tested to standard	BS EN 12897:2006	Warranty terms (Year)	1Y
No heat exchangers	1	Heat loss	1.87
Coil 1 rating (kW)	96.55	Coil 1 surface area (m ²)	2.8
Coil 1 max prim pressure (Bar)	3.5	Coil 1 resistance (Bar)	.23



Dimensions

A (mm)	1150
B (mm)	600
C (mm)	218
D (mm)	793
E (mm)	283
F (mm)	433
G (mm)	883
I (mm)	233

