

Specification

Fiche

Label

Product Specification

Product Code: TCIMVG-0400LFC

Item Description: 400L SOL TWIN HG STANDARD C



- Manufactured from high grade Duplex stainless steel
- Fitted with Branded Quality Components
- Works with Air Source Heatpumps

Capacity	Brand	ERP Type	Item Category Code	Product Group Code	Model
400 L	CYCLONE	IndirectUnvented	Stainless	CYCLONE	HG SOLAR

Product Specification

Actual capacity (Ltr)	371	Thermal insulation	DENSE PU FOAM
Unit weight empty (kg)	84	Cylinder material	LDX 2101
Unit weight full (kg)	486	Outer casing	COATED MILD STEEL
No immersions	1	Coil material	316L STAINLESS STEEL
Immersion spec	3KW@230V	Foam thickness	50
Max mains water pressure (Bar)	10	Operating temp (C)	60
Operating pressure (Bar)	7	Safety valve temp (C)	95
Tested to standard	BS EN 12897:2006	Warranty terms (Year)	25Y
No heat exchangers	2	Heat loss	2.45
Coil 1 rating (kW)	23	Coil 2 rating (kW)	53
Coil 1 surface area (m ²)	.77	Coil 2 surface area (m ²)	3.5
Coil 1 max prim pressure (Bar)	3.5	Coil 2 max prim pressure (Bar)	3.5
Coil 1 resistance (Bar)	.06	Coil 2 resistance (Bar)	.1



Talk to our sales and distribution partner today.

01271 850 204 • sales@energylabuk.com

energylabuk.com • @the-energy-lab-solutions

Supporting you at every install.

Registered Address: Millennium House, Brannam Crescent, Roundswell Business Park, Barnstaple, Devon, EX31 3TD United Kingdom | Company Number: 08586990